

Welvaartstraat 14–B2200 HERENTALS

EAN code Bag	5410797700123
EAN code cart./Technifil	5410797700116
EAN code Palet	



TECHNICAL SHEET

Capacity	
Top Out	140 x 114
Top In	
Base	
Useful Height	
Total Height	
Net Weight	6,02
Model	LK (2)
Gauge	460
Alloy (*0)	ALU/PE/KARTON
Lubrication	
Holes	NO
Diameter	
Colors in/out	
Rolled edge	
Temperature	

LK-CH0500-10X100

#Pcs pro carton:	1000
#Pcs pro bag	100
#Bags pro carton	10
#Cartons pro palette	100
#Cartons pro layer	10
#Layers Pro palette	10
#Pcs pro palette	100000
Carton dimension L.D.H	330 x 250 x 215 mm
Tare carton (kg)	0,28
Net carton (kg)	6,02
Gross carton (kg)	6,30
Gross palette (kg)	660,00
Palette height (meter)	1,70
Country of Production	(10)

FOR DETAILED INFORMATION CONSULT our: “Declaration of Conformity for LIDS ALU KARTON”

Made of materials that complies with :

- * Regulation 2004/1935/EC on material and articles intended to come into contact with food and 2023/2006/EC on Good Manufacturing Practice.
- * Regulation 10/2011/EC on plastic materials and articles intended to come into contact with food
- * Regulation 94/62/EC on packaging and packaging waste
- * With regard to the contents of heavy metals, the provisions of Directive 94/62 EC (including the amendment Directives 2004/12 EC and 2005/20 EC) are adhered to.
- * The KARTON lids correspond to the current Version of Directive (EG) Nr. 1907/2006. It is assured that no high concern materials as part of the Version of Directive (EG) Nr. 1907/2006 are included. Based on the valid "Candidate List of Substances of Very High Concern" (SVHC-List).
- * Belgium: Royal Decree 12 June 2017 adapting Royal Decree 11 Mai 1992 on FCM.
- * Netherlands : « Warenwetregeling verpakking en gebruiksartikelen », 328583-11560-VGP.
- * Product is free of GMO, allergens, nanoparticles, Bisphenol A and are of non-animalorigin.

Proper conditions of transport, storage and use:

- * Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
- * Avoid moisture (wetness, condensation, ...).

ATTENTION : Not convenient for use in microwave/oven - remove lid from container before heating container in oven/microwave

Tolerances :
thickness and weight +/- 8%
dimensions +/- 1,5 mm

- (0) Or equivalent
(1) Lubricant approved for food contact, the amount used depends on the shape and complexity of the tray.
(2) Rectangular model
(3) Round model

- (9) Produced in Belgium by Aluvin
(10) Produced in Europe for Aluvin

Version 8
Creation date: 16/07/2020
Expiry date: 16/07/2023
or by next version

