

## TECHNICAL SHEET

Capacity	
Top Out	227 x 118
Top In	
Base	238 x 190
Useful Height	0
Total Height	8
Net Weight	6,86
Model	LA (6)
Gauge	40
Alloy (*0)	8006 H24/3003 H24
Lubrication	(1)
Holes	NO
Diameter	
Colors in/out	
Rolled edge	
Temperature	

## LA-SM-5X100

Welvaartstraat 14–B2200 HERENTALS

EAN code Bag	5410797603424
EAN code cart./Technifil	5410797603417
EAN code Palet	



#Pcs pro carton:	500
#Pcs pro bag	100
#Bags pro carton	5
#Cartons pro palette	98
#Cartons pro layer	14
#Layers Pro palette	7
#Pcs pro palette	49000
Carton dimension L.D.H	275 x 225 x 240 mm
Tare carton (kg)	0,20
Net carton (kg)	3,43
Gross carton (kg)	3,63
Gross palette (kg)	386,13
Palette height (meter)	1,80
Country of Production	(9)

**FOR DETAILED INFORMATION CONSULT our: “Declaration of Conformity for Aluminium Foil Containers and Lids”**

**Made of materials that complies with :**

- \* Regulation **2004/1935/EC** on material and articles intended to come into contact with food and 2023/2006/EC on Good Manufacturing Practice.
- \* European Standard **EN602/2005** "Aluminium and aluminium alloys - Wrought products - Chemical Composition of semi products used for the fabrication of articles for use in contact with food.
- \* Belgium: Royal Decree 12 June 2017 adapting Royal Decree 11 Mai 1992 on FCM.
- \* France: Arrête du 17/8/1987 relatif aux matériaux et objets en aluminium ou en alliages d'aluminium au contacts des denrées, produits et boissons alimentaire ; DGCCRF document DM/4B/COM/001, fiche MCDA n°2B, version 1/1/2016
- \* Netherlands : « Warenwetregeling verpakking en gebruiksartikelen », 328583-11560-VGP.
- \* Product is free of GMO, allergens, nanoparticles, Bisphenol A and are of non-animalorigin.

**Proper conditions of transport, storage and use:**

- \* Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
- \* Avoid moisture (wetness, condensation, ...).
- \* Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms. Open packaging 2-3 hours prior to use.
- \* Aluminium tray can be used within temperature range : -40°C / +350°C (max 60 min). However, content of filled containers can influence these limits. Always remove lid before putting it into the oven.
- \* It is recommended to avoid contact with strongly acidic and/or alkaline products and salty foods.
- \* The suitability of uncoated aluminium foil containers for specific applications should be ascertained by the relevant user/customer/packer.

**Tolerances :**  
thickness (EN546-3) and weight +/- 8%  
dimensions +/- 1 mm pro side

- (0) Or equivalent
- (1) Lubricant approved for food contact, the amount used depends on the shape and complexity of the tray.
- (2) Rectangular model with vertical edge.
- (3) Rectangular model with rolled edge.
- (4) Round model with vertical edge
- (5) Round Model with rolled edge.
- (6) Lid Aluminium
- (7) Smooth Wall
- (8) Special forms.
- (9) Produced in Belgium by Aluvin
- (10) Produced in Europe for Aluvin

Version 8  
Creation date: 16/072020  
Expiry date: 16/07/2023  
or by next version

