

TECHNICAL SHEET

Capacity	500 cc
Top Out	144 x 119
Top In	131 x 107
Base	108 x 84
Useful Height	45
Total Height	55
Net Weight	6,95
Model	CH (2)
Gauge	58
Alloy (*0)	8006 H24
Lubrication	(1)
Holes	NO
Diameter	
Colors in/out	
Rolled edge	2,2 mm
Temperature	-40°C-350°C

Welvaartstraat 14–B2200 HERENTALS

EAN code Bag	5410797300125
EAN code cart./Technifil	5410797300118
EAN code Palet	



CH0500 10x100

#Pcs pro carton:	1000
#Pcs pro bag	100
#Bags pro carton	10
#Cartons pro palette	32
#Cartons pro layer	4
#Layers Pro palette	8
#Pcs pro palette	32000
Carton dimension L.D.H	490 x 400 x 261 mm
Tare carton (kg)	0,54
Net carton (kg)	6,95
Gross carton (kg)	7,49
Gross palette (kg)	269,68
Palette height (meter)	2,28
Country of Production	(9)

FOR DETAILED INFORMATION CONSULT our: "Declaration of Conformity for Aluminium Foil Containers and Lids"

Made of materials that complies with :

- * Regulation **2004/1935/EC** on material and articles intended to come into contact with food and 2023/2006/EC on Good Manufacturing Practice.
- * European Standard **EN602/2005** "Aluminium and aluminium alloys - Wrought products - Chemical Composition of semi products used for the fabrication of articles for use in contact with food.
- * Belgium: Royal Decree 12 June 2017 adapting Royal Decree 11 Mai 1992 on FCM.
- * France: Arrête du 17/8/1987 relatif aux matériaux et objets en aluminium ou en alliages d'aluminium au contacts des denrées, produits et boissons alimentaire ; DGCCRF document DM/4B/COM/001, fiche MCDA n°2B, version 1/1/2016
- * Netherlands : « Warenwetregeling verpakking en gebruiksartikelen », 328583-11560-VGP.
- * Product is free of GMO, allergens, nanoparticles, Bisphenol A and are of non-animalorigin.

Proper conditions of transport, storage and use:

- * Long-term storage at 12-24°C and short-term transport at 10-35°C, in an atmosphere as dry as possible.
- * Avoid moisture (wetness, condensation, ...).
- * Allow 2-3 days in intermediate storage, when moving from cold to warm or damp processing rooms. Open packaging 2-3 hours prior to use.
- * Aluminium tray can be used within temperature range : -40°C / +350°C (max 60 min). However, content of filled containers can influence these limits. Always remove lid before putting it into the oven.
- * It is recommended to avoid contact with strongly acidic and/or alkaline products and salty foods.
- * The suitability of uncoated aluminium foil containers for specific applications should be ascertained by the relevant user/customer/packer.

Tolerances : thickness (EN546-3) and weight +/- 8% dimensions +/- 1 mm pro side

- (0) Or equivalent
- (1) Lubricant approved for food contact, the amount used depends on the shape and complexity of the tray.
- (2) Rectangular model with vertical edge.
- (3) Rectangular model with rolled edge.
- (4) Round model with vertical edge
- (5) Round Model with rolled edge.
- (6) Lid Aluminium
- (7) Smooth Wall
- (8) Special forms.
- (9) Produced in Belgium by Aluvin
- (10) Produced in Europe for Aluvin

Version 8
Creation date: 16/072020
Expiry date: 16/07/2023
or by next version

